# A Certified Reduction Strategy for Homological Image Processing\*

M. Poza, C. Domínguez, J. Heras, and J. Rubio

Department of Mathematics and Computer Science, University of La Rioja

19 September 2014 PROLE'14

<sup>\*</sup>Partially supported by Ministerio de Educación y Ciencia, project MTM2009-13842-C02-01, and by European Commission FP7, STREP project ForMath, n. 243847

### Goal

### Goal

A formally-verified and efficient method to analyse digital images.

### Goal

### Goal


A formally-verified and efficient method to analyse digital images.

### A motivating example: counting synapses


- Synapses are the points of connection between neurons.
- Relevance: Computational capabilities of the brain.
- Procedures to modify the synaptic density may be an important asset in the treatment of neurological diseases.
- An automated, efficient, and reliable method is necessary.



# Counting Synapses



# Counting Synapses




# **Counting Synapses**




### Digital Image










# Digital Image Simplicial Complex

### Homology groups

$$\begin{array}{c} H_0 = \mathbb{Z} \oplus \mathbb{Z} \\ H_1 = \mathbb{Z} \oplus \mathbb{Z} \oplus \mathbb{Z} \end{array}$$

 $C_0 = \text{vertices}$   $C_1 = \text{edges}$   $C_2 = \text{triangles}$ Chain Complex



### Interactive Proof Assistants

- What is an Interactive Proof Assistant?
  - Software tool for the development of formal proofs.
  - Man-Machine collaboration:
    - Human: design the proofs.
    - Machine: fill the gaps.
  - Examples: Isabelle, Hol, ACL2, Coq, ...

### Interactive Proof Assistants

- What is an Interactive Proof Assistant?
  - Software tool for the development of formal proofs.
  - Man-Machine collaboration:
    - Human: design the proofs.
    - Machine: fill the gaps.
  - Examples: Isabelle, Hol, ACL2, Coq, ...
- Applications:
  - Mathematical proofs:
    - Four Colour Theorem.
    - Feit-Thompson Theorem.
    - Kepler conjecture.
  - Software and Hardware verification:
    - C compiler.
    - AMD5K86 microprocessor.
    - seL4: operating-system kernel.



# Coq/SSReflect

- Coq:
  - An Interactive Proof Assistant.
  - Based on Calculus of Inductive Constructions.
  - Interesting feature: program extraction from a constructive proof.

# Coq/SSReflect

### Coq:

- An Interactive Proof Assistant.
- Based on Calculus of Inductive Constructions.
- Interesting feature: program extraction from a constructive proof.

### SSReflect:

- Extension of Coq.
- Developed while formalising the Four Colour Theorem by G. Gonthier.
- It has been used in the formalisation of the Feit-Thompson Theorem.



### **Problem**

### Goal

A formally-verified (using Coq) and efficient method (from Algebraic Topology) to analyse digital images.

### Problem

### Goal

A formally-verified (using Coq) and efficient method (from Algebraic Topology) to analyse digital images.

### Problem

Cog is not designed for computing, but for proving.



### Problem

### Goal

A formally-verified (using Coq) and efficient method (from Algebraic Topology) to analyse digital images.

### Problem

Coq is not designed for computing, but for proving.

Demo.




### Outline

- A Reduction Algorithm
- 2 The Role of Haskell
- Conclusions and Further Work

### Outline

- A Reduction Algorithm
- 2 The Role of Haskell
- Conclusions and Further Work


### General Idea





J. Heras, M. Dénès, G. Mata, A. Mörtberg, M. Poza, and V. Siles. Towards a certified computation of homology groups. In proceedings 4th International Workshop on Computational Topology in Image Context. Lecture Notes in Computer Science, 7309, pages 49-57, 2012.

### General Idea



### Concrete Goal

Formalise an algorithm that reduces the information but keeps the homological properties.





































- From a digital image, we construct 2 incidence matrices:
  - Vertex-Edge matrix.
  - Edge-Triangle matrix.





- From a digital image, we construct 2 incidence matrices:
  - Vertex-Edge matrix.
  - Edge-Triangle matrix.
- Compute an admissible discrete vector field dvf.





- From a digital image, we construct 2 incidence matrices:
  - Vertex-Edge matrix.
  - Edge-Triangle matrix.
- Compute an admissible discrete vector field dvf.
- Use *dvf* to reduce the matrices:
  - Vertex-Edge matrix:  $16 \times 32 \Rightarrow 1 \times 1$ .
  - Edge-Triangle matrix:  $32 \times 16 \Rightarrow 1 \times 0$ .

### Formalised Results

Two main results have been formalised:

- The Coq's implementation of Romero-Sergeraert's is correct.
- Given incidence matrices and a discrete vector field for them, we can reduce the size of the matrices preserving their homological properties.

### Formalised Results

### Two main results have been formalised:

- The Coq's implementation of Romero-Sergeraert's is correct.
- Given incidence matrices and a discrete vector field for them, we can reduce the size of the matrices preserving their homological properties.

### Coq development:

• 45,000 lines of code, 2,500 theorems, and 1,700 definitions.

### Formalised Results

### Two main results have been formalised:

- The Coq's implementation of Romero-Sergeraert's is correct.
- Given incidence matrices and a discrete vector field for them, we can reduce the size of the matrices preserving their homological properties.

### Coq development:

• 45,000 lines of code, 2,500 theorems, and 1,700 definitions.

### Coq development about homology of digital images:

• 3,800 lines of code, 260 theorems, and 200 definitions.



### Outline

- A Reduction Algorithm
- 2 The Role of Haskell
  - Fast Proof Prototyping
  - Improving the Performance of the Computations
- Conclusions and Further Work

### Outline

- A Reduction Algorithm
- 2 The Role of Haskell
  - Fast Proof Prototyping
  - Improving the Performance of the Computations
- Conclusions and Further Work

# Fast Proof Prototyping

### 3rd Workshop on Mechanizing Metatheory (2008)

"The use of proof assistants in programming language research is still not commonplace: the available tools are confusingly diverse, difficult to learn, inadequately documented, and lacking in specific library facilities required for work in programming languages."

# Fast Proof Prototyping

### 3rd Workshop on Mechanizing Metatheory (2008)

"The use of proof assistants in programming language research is still not commonplace: the available tools are confusingly diverse, difficult to learn, inadequately documented, and lacking in specific library facilities required for work in programming languages."

Proof assistants have improved in the last few years, but they are not there yet.

- Haskell as programming language.
- QuickCheck to test the programs.
- Cog/SSReflect to verify the correctness of the programs.

#### Haskell:

#### Algorithm (gen\_adm\_dvf)

Input: A matrix M.

Output: An admissible discrete vector field for M.

17/24

#### Haskell:

#### Algorithm (gen\_adm\_dvf)

Input: A matrix M.

Output: An admissible discrete vector field for M.

#### QuickCheck:

- A specification of the properties which our program must verify.
- Testing them:
  - Towards verification.
  - Detect bugs in early stages.
- > quickCheck M -> admissible (gen\_adm\_dvf M)
- + + + OK, passed 100 tests

#### Haskell:

#### Algorithm (gen\_adm\_dvf)

Input: A matrix M.

Output: An admissible discrete vector field for M.

#### QuickCheck:

- A specification of the properties which our program must verify.
- Testing them:
  - Towards verification
  - Detect bugs in early stages.

```
> quickCheck M -> admissible (gen_adm_dvf M)
```

+ + + OK, passed 100 tests

#### Coq/SSReflect:

#### SSReflect Theorem:

```
Theorem gen_adm_dvf_is_admissible (M : seq (seq Z2)) :
admissible (gen_adm_dvf M).
```

### Outline

- A Reduction Algorithm
- 2 The Role of Haskell
  - Fast Proof Prototyping
  - Improving the Performance of the Computations
- Conclusions and Further Work

# How much is the performance improved?

#### 500 randomly generated matrices:

- Initial size of the matrices:  $100 \times 300$ .
- Time: 12 seconds.

# How much is the performance improved?

#### 500 randomly generated matrices:

- Initial size of the matrices:  $100 \times 300$ .
- Time: 12 seconds.

#### After reduction:

- Size of matrices:  $5 \times 50$ .
- Time: milliseconds

# How much is the performance improved?

#### 500 randomly generated matrices:

- Initial size of the matrices:  $100 \times 300$ .
- Time: 12 seconds.

#### After reduction:

- Size of matrices:  $5 \times 50$ .
- Time: milliseconds.

#### Problem

For bigger matrices, the reduction process takes a lot of time.

19/24

Use Haskell as an Oracle:

Detect computational bottlenecks.

- Detect computational bottlenecks.
- 2 When an expensive computation is required, call Haskell.

- Detect computational bottlenecks.
- 2 When an expensive computation is required, call Haskell.
- 3 Check in Coq that the result is correct.

- Detect computational bottlenecks.
- 2 When an expensive computation is required, call Haskell.
- 3 Check in Coq that the result is correct.
- Continue the computation in Coq.

#### Use Haskell as an Oracle:

- 1 Detect computational bottlenecks.
- 2 When an expensive computation is required, call Haskell.
- Oheck in Coq that the result is correct.
- Ontinue the computation in Coq.

#### Example (Inverse of a matrix):

- Problem related to handling big datastructures.
- Given a matrix M, compute (in Haskell) its inverse matrix  $M_1$ .
- Prove in Coq that  $M \times M_1 = 1$  (by compute).
- Continue the computation in Coq.

### Outline

- A Reduction Algorithm
- 2 The Role of Haskell
- Conclusions and Further Work

### Conclusions and Further Work

- Conclusions:
  - Formalisation of reduction algorithm for digital images.
  - Methodology to overcome efficiency problems.

## Conclusions and Further Work

- Conclusions:
  - Formalisation of reduction algorithm for digital images.
  - Methodology to overcome efficiency problems.
- Further work:
  - Obtain better performance:
    - Improve algorithms.
    - Implement more efficient data structures.
    - Improve the running environments in proof assistants.
    - Extract certified code from Coq.
  - Apply methodology and techniques to:
    - Persistent homology and Zigzag persistence.
    - Application: automate the location of neuronal structure from a stack of images.



# Bibliography about this work

- M. Poza (2013): Certifying homological algorithms to study biomedical images. Ph.D. thesis, University of La Rioja.
- M. Poza, C. Domínguez, J. Heras, and J. Rubio (2014): A certified reduction strategy for homological image processing. ACM Transactions on Computational Logic 15(3).
- M. Poza, C. Domínguez, J. Heras, and J. Rubio (2014): A certified reduction strategy for homological image processing. Arxiv: http://arxiv.org/abs/1306.0806.
- M. Poza, C. Domínguez, J. Heras, and J. Rubio (2014): http://www.unirioja.es/cu/cedomin/crship/.

# A Certified Reduction Strategy for Homological Image Processing

M. Poza, C. Domínguez, J. Heras, and J. Rubio

Department of Mathematics and Computer Science, University of La Rioja

19 September 2014 PROLE'14

