WekaBioSimilarity — extending Weka with resemblance measures*

C. Domínguez, J. Heras, E. Mata, and V. Pascual

Department of Mathematics and Computer Science, University of La Rioja


15 September 2016 TAMIDA'16

^{*}Partially supported by the Agencia de Desarrollo Económico de La Rioja (ADER) [2013-I-IDD-00123] and


Resemblance-analysis is an important concern in several fields



Resemblance-analysis is an important concern in several fields



Resemblance-analysis is an important concern in several fields




Depend on the concrete problem

Different types of features: binary, multi-value (nominal), string, or numerical



Resemblance-analysis is an important concern in several fields




Several resemblance (similarity and distance) measures have been proposed



S. S. Choi et al. *A survey of binary similarity and distance measures*. Journal of Systemics, Cybernetics and Informatics 8(1),43–48. 2010.



Resemblance-analysis is an important concern in several fields



Clustering algorithms

Hierarchical clustering can be visualised using a tree representation

Problem

Several statistical packages (e.g. R, Matlab, Octave, Weka, or SPSS) provide the functionality for resemblance analysis




Problem

Several statistical packages (e.g. R, Matlab, Octave, Weka, or SPSS) provide the functionality for resemblance analysis

- Problem: they only support binary/or numerical features
- They cannot handle:
 - Comparison of DNA sequences (multi-value/string descriptors)
 - DNA fingerprints (numerical feature vectors)
 - Phylogenetic or data mining (heterogeneous descriptors)
 - . . .



Solution



WekaBioSimilarity:

- Extends Weka with resemblance measures and comparison modes
- Works with binary, numerical, nominal, and heterogeneous data
- Open, easily extensible and integrable with other systems



Outline

- Introduction
- Resemblance measures in WekaBioSimilarity
- 3 Integration of WekaBioSimilarity in Weka
- 4 Conclusions

SPECT heart dataset:

Patient	F1	F2	F3	F4	F5	F6	F7	F8	F9	F10
P1	Yes	Yes	No	No	Yes	Yes	No	No	No	Yes
P2	Yes	Yes	No	No	Yes	Yes	No	No	No	No
P3	Yes	No	No	No	Yes	No	Yes	No	No	Yes
P4	Yes	No	Yes	Yes	Yes	No	No	Yes	No	Yes
P5	Yes	No	No	Yes	No	No	No	No	Yes	No

SPECT heart dataset:

Patient	F1	F2	F3	F4	F5	F6	F7	F8	F9	F10
P1	Yes	Yes	No	No	Yes	Yes	No	No	No	Yes
P2	Yes	Yes	No	No	Yes	Yes	No	No	No	No
P3	Yes	No	No	No	Yes	No	Yes	No	No	Yes
P4	Yes	No	Yes	Yes	Yes	No	No	Yes	No	Yes
P5	Yes	No	No	Yes	No	No	No	No	Yes	No

Given two objects A and B, four values are computed:

- $M_{11} = \sharp$ attributes present both in A and B
- $M_{10}=\sharp$ attributes present in A but not in B
- ullet $M_{01}=\sharp$ attributes present in B but not in A
- $M_{00} = \sharp {
 m attributes}$ present neither in A nor in B

SPECT heart dataset:

 Patient
 F1
 F2
 F3
 F4
 F5
 F6
 F7
 F8
 F9
 F10

 P1
 Yes
 Yes
 No
 No
 Yes
 Yes
 No
 No
 Yes
 No
 No
 No
 Yes
 No
 No
 No
 Yes
 Yes
 No
 Yes
 No
 <td

Given two objects A and B, four values are computed:

- $M_{11} = \sharp$ attributes present both in A and B
- ullet $M_{10}=\sharp$ attributes present in A but not in B
- $M_{01}=\sharp$ attributes present in B but not in A
- ullet $M_{00}=\sharp$ attributes present neither in A nor in B

Resemblance measures are computed from those values:

$$S(A,B) = \frac{M_{11} + M_{00}}{M_{11} + M_{10} + M_{01} + M_{00}}$$

SPECT heart dataset:

 Patient
 F1
 F2
 F3
 F4
 F5
 F6
 F7
 F8
 F9
 F10

 P1
 Yes
 Yes
 No
 No
 Yes
 Yes
 No
 No
 Yes
 No
 No

Given two objects A and B, four values are computed:

- ullet $M_{11}=\sharp$ attributes present both in A and B
- ullet $M_{10}=\sharp$ attributes present in A but not in B
- ullet $M_{01}=\sharp$ attributes present in B but not in A
- $M_{00} = \sharp$ attributes present neither in A nor in B

Resemblance measures are computed from those values:

$$S(A,B) = \frac{M_{11} + M_{00}}{M_{11} + M_{10} + M_{01} + M_{00}}$$

WekaBioSimilarity features 76 binary resemblance measures



HIV-1 protease cleavage dataset:

I1: AAAKFERQ

I2: AAAMKRHG

I3: AAAMSSAI

HIV-1 protease cleavage dataset:

- I1: AAAKFERQI2: AAAMKRHGI3: AAAMSSAI
- Length of feature vectors is the same
- Position of attributes in feature vectors is important

HIV-1 protease cleavage dataset:

- I1: AAAKFERQI2: AAAMKRHGI3: AAAMSSAI
- Length of feature vectors is the same
- Position of attributes in feature vectors is important
- Given two objects A and B, agreements and disagreements are computed

HIV-1 protease cleavage dataset:

- I1: AAAKFERQI2: AAAMKRHGI3: AAAMSSAI
- Length of feature vectors is the same
- Position of attributes in feature vectors is important
- Given two objects A and B, agreements and disagreements are computed
- Resemblance measures are computed from those values:

$$S(A, B) = \frac{agreements}{agreements + disagreements}$$

HIV-1 protease cleavage dataset:

- I1: AAAKFERQI2: AAAMKRHGI3: AAAMSSAI
- Length of feature vectors is the same
- Position of attributes in feature vectors is important
- Given two objects A and B, agreements and disagreements are computed
- Resemblance measures are computed from those values:

$$S(A, B) = \frac{agreements}{agreements + disagreements}$$

 WekaBioSimilarity features 25 resemblance measures (generalised from the binary case)

USDA plants database:

```
abelia: fl, nc
abelia x grandiflora: fl, nc
abel.: ct, dc, fl, hi, il, ky, la, md, mi, ms
abel. esc.: ct, dc, fl, il, ky, la, md, mi, ms
```

USDA plants database:

```
abelia: fl, nc
abelia x grandiflora: fl, nc
abel.: ct, dc, fl, hi, il, ky, la, md, mi, ms
abel. esc.: ct, dc, fl, il, ky, la, md, mi, ms
```

- Size of feature vectors might be different
- Position of attributes is not relevant

USDA plants database:

```
abelia: fl, nc
abelia x grandiflora: fl, nc
abel.: ct, dc, fl, hi, il, ky, la, md, mi, ms
abel. esc.: ct, dc, fl, il, ky, la, md, mi, ms
```

- Size of feature vectors might be different
- Position of attributes is not relevant
- Given A and B, $|S_A \cap S_B|$, $|S_A \setminus S_B|$ and $|S_B \setminus S_A|$ are used to compute resemblance measures:

$$S(A, B) = \frac{|S_A \cap S_B|}{|S_A \cap S_B| + |S_A \setminus S_B| + |S_B \setminus S_A|}$$

USDA plants database:

```
abelia: fl, nc
abelia x grandiflora: fl, nc
abel.: ct, dc, fl, hi, il, ky, la, md, mi, ms
abel. esc.: ct, dc, fl, il, ky, la, md, mi, ms
```

- Size of feature vectors might be different
- Position of attributes is not relevant
- Given A and B, $|S_A \cap S_B|$, $|S_A \setminus S_B|$ and $|S_B \setminus S_A|$ are used to compute resemblance measures:

$$S(A,B) = \frac{|S_A \cap S_B|}{|S_A \cap S_B| + |S_A \setminus S_B| + |S_B \setminus S_A|}$$

 WekaBioSimilarity features 76 resemblance measures (the same as in the binary case)

Three cases:

• Typically: Euclidean distance, Pearson correlation, and so on

Three cases:

- Typically: Euclidean distance, Pearson correlation, and so on
- Pairwise comparison (e.g. compare regions based on age demographics)
- Set occurrence (e.g. classify DNA fingerprints)

Three cases:

- Typically: Euclidean distance, Pearson correlation, and so on
- Pairwise comparison (e.g. compare regions based on age demographics)
- Set occurrence (e.g. classify DNA fingerprints)

First case available in Weka and most statistical packages

Three cases:

- Typically: Euclidean distance, Pearson correlation, and so on
- Pairwise comparison (e.g. compare regions based on age demographics)
- Set occurrence (e.g. classify DNA fingerprints)

First case available in Weka and most statistical packages Last two cases only available on WekaBioSimilarity


Three cases:

- Typically: Euclidean distance, Pearson correlation, and so on
- Pairwise comparison (e.g. compare regions based on age demographics)
- Set occurrence (e.g. classify DNA fingerprints)


First case available in Weka and most statistical packages Last two cases only available on WekaBioSimilarity Notion of closeness: tolerance value

Comparison of DNA patterns

Comparison of DNA patterns



Comparison of DNA patterns



Comparison of DNA patterns


DNA	DNA	DNA	DNA	DNA
Pattern 1	Pattern 2	Pattern 3	Pattern 4	Pattern 5
120.5 83.1 72.4 31.3	121.4 82.5 74.2 29.9	120.1 71.7 31.2	121 32.4	121.7

Values are different, but they are close enough (tolerance)

Comparison of DNA patterns

DNA	DNA	DNA	DNA	DNA
Pattern 1	Pattern 2	Pattern 3	Pattern 4	Pattern 5
120.5 83.1 72.4 31.3	121.4 82.5 74.2 29.9	120.1 71.7 31.2	121 32.4	121.7

Values are different, but they are close enough (tolerance)



Heterogeneous data

Attributes that describe an object may have different types:

• E.g. Numerical taxonomy (attributes like presence of hair, habitat, number of limbs, ...)

Heterogeneous data

Attributes that describe an object may have different types:

- E.g. Numerical taxonomy (attributes like presence of hair, habitat, number of limbs, ...)
- Only pairwise comparison can be applied

Heterogeneous data

Attributes that describe an object may have different types:

- E.g. Numerical taxonomy (attributes like presence of hair, habitat, number of limbs, ...)
- Only pairwise comparison can be applied
- WekaBioSimilarity implements 25 measures

Outline

- Introduction
- Resemblance measures in WekaBioSimilarity
- 3 Integration of WekaBioSimilarity in Weka
- 4 Conclusions

Integration of WekaBioSimilarity in Weka



Integration of WekaBioSimilarity in Weka



Outline

- Introduction
- Resemblance measures in WekaBioSimilarity
- 3 Integration of WekaBioSimilarity in Weka
- 4 Conclusions



Conclusions

Resemblance analysis:

- common problem in several contexts
- highly dependent on computing resemblance among objects
- usually special-purpose packages are necessary



Conclusions

Resemblance analysis:

- common problem in several contexts
- highly dependent on computing resemblance among objects
- usually special-purpose packages are necessary

WekaBioSimilarity:

- features the same binary measures that other packages
- generalises binary measures to other types of descriptors
- provides tolerance for numerical data
- supports two comparison modes



Conclusions

Resemblance analysis:

- common problem in several contexts
- highly dependent on computing resemblance among objects
- usually special-purpose packages are necessary

WekaBioSimilarity:

- features the same binary measures that other packages
- generalises binary measures to other types of descriptors
- provides tolerance for numerical data
- supports two comparison modes

Result:

- a tool applicable in a wide-variety of problems
- used as a standalone application or integrated in other software



WekaBioSimilarity — extending Weka with resemblance measures

C. Domínguez, J. Heras, E. Mata, and V. Pascual

Department of Mathematics and Computer Science, University of La Rioja

15 September 2016 TAMIDA'16